SPRING-TINE CULTIVATORS



Spring Tiller CM-P3F

The CM-P3F is a tiller designed for use with tractors that have a power rating between 140 and 300 HP. Its 3-row configuration with increased row spacing makes it ideal for operating at high speeds without the risk of clogging, even in the presence of abundant crop residues.

Key Features

· Anti-Clogging Design: The three-row design guarantees optimal residue management and increased working speeds.

· Flexible Frame: Made from high-strength steel and reinforced with leaf springs, it is flexible, requires less maintenance and is less prone to breakage.

· Total Adaptability: The independent working units allow the machine to excel on stony, loose or very heavy soils.

· Intelligent Spring System: It reduces tractor slippage, increases traction, and absorbs vibrations to improve comfort and fuel economy.

Agronomic Results

· Deep Tillage: It reaches a depth of 25 cm, breaking up the plough pan while leaving the soil structure intact.

· Efficiency in a Single Pass: It breaks up large clods of soil and promotes aeration and water penetration in a single pass.

· Natural Weed Control: It exposes the roots of weeds to the elements, which naturally depletes their vitality.

This model is a sound investment for those who require high productivity and maximum durability.

Technical Data

Model	**Folding**	**Overall Width**	**Row spacing**	**Working width**	**Working depth**	**Weight**	**Power**
	TIPO	CM	CM	CM	CM	KG	HP
CM-9/13P3F	IDRAULICO	239	25	342	25	1400	140
CM-11/15P3F	IDRAULICO	289	25	392	25	1700	180
CM-11/17P3F	IDRAULICO	289	25	442	25	2000	200
CM-11/19P3F	IDRAULICO	289	25	492	25	2300	220
CM-11/21P3F	IDRAULICO	289	25	540	25	2600	300
CM-13/21P3F	IDRAULICO	339	25	540	25	2550	300

Optional accessories

Harrow Attachments