SPRING-TINE CULTIVATORS

The CM-LM is the ideal machine for shallow tillage and seedbed preparation. Designed for use with tractors ranging from 50 to 80 HP, it can be used with great flexibility on loose, heavy or stony soils.

Key Features

· Compact Design: The short hitch keeps the implement close to the tractor, drastically improving manoeuvrability and stability.

· Dynamic Spring System: It reduces tractor slip and converts soil resistance into forward speed, ensuring significant fuel savings.

· Precision Work: The sharp-edged tines and independent working bodies break up large clods without altering the soil's stratigraphy.

· Environmentally Friendly: It aerates the soil, thereby promoting natural fertility and the management of organic matter, as well as ensuring uniform water penetration.

Advantages and Performance

· Optimal Depth: It is effective up to a depth of 25 cm and preserves the soil?s biological balance.

· Maximum Comfort: The spring system absorbs vibrations, making driving smoother and safer for the operator.

· Guaranteed Durability: The high-strength steel frame ensures minimal maintenance costs and a long service life.

· Single-Pass Effectiveness: Field tests have confirmed the system's excellent mulching capacity and weed control performance when exposed to the elements.

Technical Data

Model	**Folding**	**Overall Width**	**Row spacing**	**Working width**	**Working depth**	**Weight**	**Power**
	TIPO	CM	CM	CM	CM	KG	HP
CM-7LM		190	27,5	190	25	340	60
CM-7/9LM	MANUALE	187	26,5	239	25	460	70
CM-9LM		228	25	228	25	430	70
CM-9/11LM	MANUALE	228	25	278	25	560	80

Optional accessories

Harrow Attachments